



🏠 Hrabinská 498/19, 737 01
Český Těšín, Czechy

☎ +420 603 933 363

✉ email: office@valwo.eu

🌐 www.valwo.eu

V-MAX
EXPLOSION VENT

V-MAX

EXPLOSION VENT

Fike Corporation designs simple, reliable explosion protection solutions to meet your safety requirements. Fike's high performance Vmax vent features a single membrane, multi-dome surface that provides the longest service life for harsh conditions such as pulsating or cycling, higher operating pressures, and stronger vacuum. The Vmax vent has been tested to perform after 100,000 positive pressure cycles from 0 to 80% of the minimum stamped burst pressure and approximately 1,000,000 vacuum-to-positive cycles of -1 psig to 25% minimum stamped burst pressure (typical of dust collectors). Typical applications include separation, drying, storage, conveyance, and processing operations.



Explosion vent - V-MAX

FEATURES AND BENEFITS

- Inconel® Metal Tabs provide stable burst pressure ratings independent of temperature fluctuations due to process conditions or weather which in turn provides a longer service life.
- High Operating Ratio allow lower burst pressures, more flexible process conditions, and safer vent design. The Vmax vent has an operating ratio of 80% and provides a longer service life.
- Instantaneous Full Opening - reduced risk of accidental contamination due to undetected openings.
- Fail-Safe Design - certified burst pressure provides full, predictable opening at or below its rated burst pressure even if the vent is damaged.
- Dynamically tested under full-scale explosion conditions.
- 100% Venting Efficiency Optimal relief area saves money.
- Easy Installation by Plant Personnel Reduced down time and maintenance costs.
- Non-Fragmenting Design - reduced risk to personnel and equipment.

SPECIFICATIONS

Compliance:	NFPA 68
Materials of Construction :	Membrane: 316 SST Seal: PTFE
Vacuum rating:	-4.0 psig for all sizes
Maximum Operating Pressure:	80% of the minimum stamped burst pressure
Burst Pressure Tolerance:	± 0.25 psig for burst pressures 1 psig or less ± 0.50 psig for burst pressures greater than 1 psig
Operating Temperature Range:	0 - 350°F (-17 - 175°C)
Operating environment:	The vent panel is specifically designed for dry material applications. If the process vessel is to be washed out or cleaned by CIP (Clean-In-Place) or SIP (Steam-In-Place), the vent should be removed first.
Optional equipment:	Burst indicators/monitoring system; Atmospheric insulation; Process insulation; Weather covers; Flameless Venting

SPECIFICATIONS

Vent Size Inches (mm)	12 x 18 (300 x 460)	24 x 24 (610 x 610)	18 x 35 (460 x 890)	24 x 36 (610 x 910)	36 x 36 (910 x 910)	36 x 44 (910 x 1120)
Available burst pressure in psig	1.50		1.50			
	2.00	1.50	2.00	1.00	1.00	.50
	2.50	2.00	2.50	1.50	1.50	1.00
	3.00	2.50	3.00	2.00	2.00	1.50
	3.50	3.00	3.50	2.50	2.50	2.00
	4.00	3.50	4.00	3.00	3.00	2.50
	4.50	4.00	4.50	3.50	3.50	
	5.00					
Vacuum Rating in psig	-4.0	-4.0	-4.0	-4.0	-4.0	-4.0
Relief Area in ft2 (m2)	1.30 (0.12)	3.67 (0.34)	4.01 (0.37)	5.59 (0.52)	8.51 (0.79)	10.45 (0.97)



VALWO s. r. o.
Hrabinská 498/19,
737 01 Český Těšín, Česká republika

+420 603 933 363
email: office@valwo.eu

website:
www.valwo.eu/en

VALWO s. r. o. informs, that this product sheet does not constitute an offer according to the law, but is only of informative character. All data available in this product sheet have been prepared basing on manufacturer's materials.
The data contained herein may be subject to change.

